

# TERRATRAK PLUS

DETAILS	SPECIFICATIONS
Usable Surface Per Tile	43.19" x 43.19" x 1.63"
Configuration	2 Tiles = 47" x 94" x 1.63"
SF Per Tile	12.95
SF Per Sheet	25.9
Sheets Per Pallet	26
Tiles Per Pallet	52
SF Per Pallet	673.4
Actual Tile Size	47" x 47" x 1.63"
Weight Per Tile	50.4 lbs
Weight Per Sheet(of 2 tiles)	100.8 lbs
Weight Per Pallet (100 lbs for pallet weight included)	2,720.8 lbs
Height Per Pallet (including 6" for pallet height)	48.38"
Pallets Per Truck (48' flatbed stacked 2 pallets high)	15
Fully Loaded Weight Per Truck	40,812
Flatbed height from ground(+/-)5'. Height of 2 pallets = 96.76". 60" + 96.76" + 1.5" = 158.26". (Load is under <u>LEGAL</u> height of 13.5'.)	(Add 1.5" for protective crown) 158.26"
Tiles Per Truck	780
SF Per Truck	10,101
Spread Load PSF	152,232.30
Temperature Range	-4°F to 113°F
Cleaning	High pressure cold/hot water spray washer (3000 PSI or greater)
Method of Manufacture	Structural foam injection moulded
Fire Requirements	See Separate Fire Test Report (available upon request)
Colors	Standard Grey / Translucent White
Material	Virgin HDPE with 30 year UV light stabilizer
Warranty	3 Year Limited Warranty including Camlocks
Life Expectancy	depends on type of use