

TERRACOVER 'V'

DETAILS	SPECIFICATIONS
Actual Size Per Tile	42.5" x 42.5" x 1.56"
Usable Surface Per Tile	39.13" x 39.13" x 1.56"
Tiles Per Sheet	4
Size Per Sheet	85" x 85" x 1.56"
Usable Surface SF Per Tile	10.63
Usable Surface SF Per Sheet	42.52
Sheets Per Pallet	17
Tiles Per Pallet	68
Usable Surface SF Per Pallet	721
Weight Per Tile	24.2 lbs
Weight Per Sheet (4 tiles)	96.8 lbs
Weight Per Pallet (100 lbs for pallet included)	1,745.6 lbs
Height Per Pallet (including 6" for pallet height = 32.52")	32.52"
Pallets Per Truck (48' flatbed stacked 3 pallets high)	21
Fully Loaded Weight Per Truck	36,656.00
Flatbed height from ground (+/-)5'. Height of 3 pallets = 97.56". (60" + 97.56" + 1.5" = 159.06" TOTAL) Load is under <u>legal</u> height of 13.5'.	(Add 1.5" for protective crown)159.06"
Tiles Per Truck	1,428
Usable SF Per Truck	15,151
Spread Load PSF	60,336.0
Temperature Range	minus 4°F to plus 104°F
Cleaning	High pressure cold water spray washer (2500 PSI or greater)
Method of Manufacture	Twin Sheet Thermoforming, using 4mm HDPE sheets, cavity filled with foamed polyurethane
Fire Requirements	See separate fire test report (available upon request)
Colors	Standard color grey, black or white
Material	High molecular weight, high density, polyethylene
Warranty	TERRACOVER "V"® is guaranteed for 5 years