

TERRAFLOR

DETAILS	SPECIFICATIONS
Size Per Tile	29.31" x 29.31" x 1.31"
Tiles Per Sheet	6
Size Per Sheet	58.62" x 87.93" x 1.31"
SF Per Tile	5.97
SF Per Sheet	35.82
Sheets Per Pallet	20
Tiles Per Pallet	120
SF Per Pallet	716.40
Weight Per Tile	11.24 lbs
Weight Per Sheet	67.44 lbs
Weight Per Pallet (100 lbs for pallet included)	1448.80 lbs
Height Per Pallet (20 x 1.31" = 26.20" + pallet height of 6" = 32.20" per pallet)	32.20"
Pallets Per Truck (48' flatbed stacked 3 pallets high)	27
Fully Loaded Weight Per Truck	39,117.60 lbs
Flatbed height from ground (+/-)5'. Height of 3 pallets = 96.60" (60" + 96.60" + 1.5" = 158.10" TOTAL) Load is under legal height of 13.5'.	
Tiles Per Truck	3,240
SF Per Truck	19,342.80 lbs
Point Load	
Spread Load	
Temperature Range	minus 4°F to 113°F
Cleaning	High pressure cold water spray washer (2500 PSI or greater)
Method of Manufacture	Injection molded using a blowing agent, which produces an engineering foam molding with strength enhancing cellular core
Fire Requirements	See separate fire test report (available upon request)
Colors	Translucent natural material, which allows the passage of light, ensuring grass growth
Material	High molecular weight, high density, polyethylene
Warranty	Guaranteed for 2 years but has a realistic life expectancy of 15-20 years