

TERRAPLAS

DETAILS	SPECIFICATIONS
Size Per Tile	3.28' x 3.28' x 2.5"
Tiles Per Sheet	4
Size Per Sheet	6.56' x 6.56' x 2.5"
SF Per Tile	10.764
SF Per Sheet	43.05
Sheets Per Pallet	18
Tiles Per Pallet	72
SF Per Pallet	775
Weight Per Tile	24 lbs
Weight Per Sheet	96 lbs
Weight Per Pallet (100 lbs for pallet included)	1,828 lbs
Height Per Pallet (18 x 2.5" = 45" + pallet height of 5" = 50" per pallet)	50" (4.16')
Pallets Per Truck (48' flatbed stacked 2 pallets high)	14
Fully Loaded Weight Per Truck	25,592 lbs
Flatbed height from ground (+/-)5'. Height of 2 pallets=8.33'. (5'+8.33'=13.33' TOTAL) Load is under legal height of 13.5'.	
Tiles Per Truck	1,008
SF Per Truck	10,850
Temperature Range	14°F to 104°F
Cleaning	High pressure cold water spray washer (2500 PSI or greater)
Method of Manufacture	Low pressure injection molding using a chemical blowing agent which produces an engineering structural foam molding with a strength enhancing cellular core
Fire Requirements	See separate fire test report (available upon request)
Colors	Natural translucent color which reflects sunlight, thereby reducing heat build-up and turf damage. Non-slip stripes are in light grey as standard, but can be provided in any color
Material	Ultra Violet light stabilized high density Polyethylene Copolymer Grade with narrow molecular weight distribution, specially developed for injection molding of heavy duty articles
Warranty	TERRAPLAS® is guaranteed for 5 years