

# TERRATILE

DETAILS	SPECIFICATIONS
Size Per Tile	39.5" x 39.5" x 1.37" (1 sq meter)
Tiles Per Sheet	4
Size Per Sheet	6.5' x 6.5' x 1.37" (2 sq meters)
SF Per Tile	10.764
SF Per Sheet	43.56
Sheets Per Pallet	20
Tiles Per Pallet	80
SF Per Pallet	871
Weight Per Tile	16.5 lbs
Weight Per Sheet (of 4 tiles)	66 lbs
Weight Per Pallet(100 lbs for pallet included)	1,420 lbs
Pallets Per Truck (48' flatbed stacked 3 pallets high)	21
Fully Loaded Weight Per Truck	29,820 lbs
Height Per Pallet (20 x 1.37" = 27.4" + pallet height of 6" = 33.4" per pallet)	33.4" (2.78')
Height Per Stack of 3 Pallets	100.2"(8.35')
Flatbed height from ground (+/-)5'. Height of 3 pallets=8.35'. (5'+8.35'=13.35' TOTAL) Load is under <u>legal</u> height of 13.5'.	
Tiles Per Truck	1680
SF Per Truck	18,291
Temperature Range	minus 22°F to plus 120°F
Cleaning	High pressure cold water spray washer (2500 PSI or greater)
Method of Manufacture	Injection molded using a blowing agent, which produces an engineering foam molding with strength enhancing cellular core
Fire Requirements	See separate fire test report (available upon request)
Colors	Opaque White
Material	High molecular weight, high density, polyethylene with UV stabilizer, allowing the passage of light; which ensures grass growth
Warranty	2 years on the panel and 1 year on the locking cams. Warranty has specific instructions regarding driving vehicles on TERRATILE®